

POWERHOUSE® PRO SERIES GENERATOR SPECS

POWERHOUSE PRO SERIES INVERTER GENERATOR SPECIFICATIONS

FEATURE	PH1000i (69270)	PH2100Pri (69271)	PH2700Pri (69272)	PH3100Pri (69273)	PH6500Pri (69274)
SPECIFICATIONS					
AC Output: Rated / Max (Watts)	900 / 1000 W	2000 / 2100 W	2600 / 2700 W	3000 / 3100 W	6000 / 6500 W
DC Output (A)	12 V-5 A	12 V-8.3 A	12 V-8.3 A	12 V-8.3 A	12 V-8.3 A
Maximum Current (A)	8.3 A	17.5 A	22.5 A	25.8 A	54 A
Maximum Engine Speed	5500 rpm	5000 rpm	5000 rpm	3600 rpm	3600 rpm
Engine Type	Single Cylinder, 4-Stroke OHV, Air Cooled Gasoline	Single Cylinder, 4-Stroke OHC, Air Cooled Gasoline		Single Cylinder, 4-Stroke OHV, Air-Cooled Gasoline	
Horsepower (hp) / Displacement	1.63hp / 53cc	4.35hp / 125cc	5.1hp / 150cc	6.8hp / 270cc	11.6hp / 420cc
Starting System	Recoil	Remote, Electric & Recoil			Remote & Electric
Continuous Run Time (hr), Full load (1/4 load) per Tankful	3.7 hrs. (9.7 hrs.)	3.2 hrs. (7.9 hrs.)	2.9 hrs. (7.2 hrs.)	5.6 hrs. (13.1 hrs.)	5.3 hrs. (12.8 hrs.)
Fuel Tank Capacity (Gal)	0.8 gal. (3.0L)	1.3 gal. (4.9L)	1.4 gal. (5.3L)	4.4 gal. (16.6L)	5.8 gal. (22.0L)
Generator Dimensions (in) (L x W x H)	18-1/8" x 9-13/16" x 15-1/8"	22" x 11" x 19"	22-3/4" x 13" x 17"	23-5/8" x 17-3/4" x 20-1/2"	32" x 28" x 29-1/2"
Dry Weight (lb.)	35.55 lbs. (16.3kg)	73 lbs. (33kg)	80 lbs. (36kg)	129 lbs. (59kg)	186 lbs. (84kg)
Noise Level, dB @23': Zero load / Full load	55 / 64 dB	56 / 66 dB	58 / 67 dB	56 / 65 dB	73 / 78 dB
Rated Current (A)	7.5 A	16.7 A	21.7 A	25 A	50 A
Rated Frequency (Hz)	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Rated Voltage (V)	120 V	120 V	120 V	120 V	120 / 240 V
Receptacles	One 120 V, 20 A 5-20R Duplex	One 120 V, 20 A 5-20R Duplex	One 120V, 20A 5-20R Split Duplex	One 120 V, 20 A 5-20R Duplex & One 120 V, 30 A L5-30R	One 120 V, 20 A 5-20R Split Duplex, One 120 V, 30 A L5-30R & One 120/240 V, 30 A L14-30R
Fuel Type	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline
Oil Capacity	8.5 oz. (250mL)	15.6 oz. (460mL)	16.9 oz. (500mL)	33.8 oz. (1.0L)	37.2 oz. (1.1L)
Oil Type	15W-40	15W-40	15W-40	15W-40	15W-40
Spark Plug	A7RTC	A7RTC	A7RTC	F7RTC	F7RTC
FEATURES					
Accessories Included	Oil Jug, 12 V Charge Cable, Spare Spark Plug, Spark Plug Wrench & Handle, Screwdriver, Manual*, 3 Quick-Start Guides*, Oil Drain Extension	Oil Jug, 12 V Charge Cable, Spare Spark Plug, Spark Plug Wrench & Handle, Screwdriver, Manual*, 3 Quick-Start Guides*, Keys & Remote, Oil Drain Extension, Spare 20A ATC Style Fuse, Internal Charging Cable			Oil Jug, 12 V Charge Cable, Spare Spark Plug, Spark Plug Wrench & Handle, Screwdriver, Manual*, 3 Quick Start Guides*, Keys & Remote, Spare 20A & 30A ATC Style Fuses
Automatic Low Oil Shutdown	Yes	Yes	Yes	Yes	Yes
Certifications	EPA, CSA, CARB, ISO	EPA, CETL, CARB, ISO, IC, FCC		EPA, CSA, CARB, ISO, IC, FCC	EPA, CETL, CARB, ISO
Choke	Manual	Auto	Auto	Auto/Elec	Auto/Elec
Electric Circuit Breaker	Inverter Controlled & Panel Mounted				
Fuel Economy Switch	Yes	Yes	Yes	Yes	Yes
Fuel Gauge	No	No	No	Yes	Yes
Hour Meter	No	No	No	Yes	Yes
Ignition System	Electronic Ignition	Electronic Ignition	Electronic Ignition	Electronic Ignition	Electronic Ignition
Inverter Equipped	Yes	Yes	Yes	Yes	Yes
Overload Reset Switch	Yes	Yes	Yes	Yes	Yes
Parallel Ready	No	Yes	Yes	No	No
Phase	Single	Single	Single	Single	Single
Primer Bulb	No	Yes	Yes	No	No
Remote Control	No	Yes	Yes	Yes	Yes
Structure	Enclosed	Enclosed	Enclosed	Enclosed	Enclosed
Wheels / Handles	No / Carry handle	Optional accessory wheel-handle kit 60408	2 fixed / Carry plus wheelie handle	2 fixed with brakes, 2 swivel / folding handle	2 fixed / 2 folding wheelbarrow handles
*Note	*Owner's Manual is in 3 parts, English, French and Spanish; 3 separate Quick Start Guides: 1 each English, French, Spanish				